


# Speed Display GR36 L•CL

ASA plastics enclosure



- ✓ Speed
- ✓ Smiley
- ✓ Text



## Highlights













- SierzeGA is proud to present its new series of Speed Displays - the **GR36** model.
- The new GR36 is a dot-matrix display that is showing **speeds** and **smiley/frowning faces** as well as **short text messages** to make drivers aware of their speed and forces them to react to it.
- As a new feature the GR36 is already equipped with **remote data access** for controlling the display from everywhere (no additional hardware necessary). Besides, the device can still be configured over **Bluetooth**. The internal GPS clock offers **local time adjustment** and **date setting** in the background.

## Colour Options

**GR36L**   
Amber LEDs  
No Data Collection

**GR36CL**   
Multi-Colour LEDs  
Data Collection

## Features

 4kg	 Bluetooth	 Speed, Smiley, short Text
 <1W	 Brightness Regulation	 Analysis Software
 IP67	 App	 Cloud (4G)
 Data Collection GR36CL only	 GPS	 Time Control

## Electrical Data

<b>Input Voltage</b>	12V
<b>Standby (Radar on, LEDs off)</b>	< 0,1W (!)
<b>Display active (speed value)</b>	< 1W

## Radar Sensor

<b>Operating Frequency</b>	Multi-target Radar K-Band (24 GHz)
<b>Transmitting Power</b>	5 mW
<b>Certification</b>	CE approved
<b>Operating Speed</b>	3 ... 255 km/h or 3 .. 200 mph
<b>Detection Range</b>	min. 100 m, avg. 200 m Truck avg. 300 m
<b>Accuracy</b>	± 3 %

## LEDs

<b>Brand</b>	Osram LEDs Black Series
<b>Color</b>	Yellow 590 nm Red, Green, mixed yellow
<b>Life Span</b>	Long Lifetime, Reliability

## Display

<b>Pixel Grid</b>	10 mm yellow 20 mm red/green
<b>Digit Size</b>	30 cm
<b>Reading Distance</b>	approx. 150 m
<b>Readability</b>	Unique contrast due to special design
<b>Update Rate</b>	approx. 1 sec, adjustable
<b>Brightness Regulation</b>	Automatically
<b>Data Collection</b>	up to 1,6 Mio records

## Mechanical Data

<b>Dimensions</b>	62 x 62 x 4 cm
<b>Weight</b>	4 kg
<b>Enclosure</b>	ASA Plastics
<b>Front Plate Sheeting</b>	Highly Reflective, White
<b>Protection Degree</b>	IP67
<b>Front Window</b>	Lexan, Anti-Glare Coating
<b>Ambient Temperature</b>	-25°C to 60°C

## Scope of Delivery

- Speed Display GR36
- Software: GRS online/Mobile App
- Pole Brackets (60 or 76 mm)
- Power supply Cable 12V
- Optional: Variable Pole Clamps
- Optional: Batteries and Solar Power Supply

